



You're always ahead... with a Modern behind!

For more information or to locate a dealer call 1-800-231-8198

**CUTTING  
WIDTH  
96"**

**THE 8' OFFSET RIGID DECK PREDATORRR IS A CAT. 2 WITH A 150 HP TRANSFER GEARBOX W/TWO 95 HP OUT BOARD GEARBOXES.**

### Warranty

Provides a 5 year limited warranty on gearbox and 10 year limited warranty on deck rust thru.



#### Features:

- 1/2" gearbox plate
- Cylinder and hoses are standard
- Heavy duty stump jumpers & slip clutch protected
- Laminated tailwheels
- Solid 3/16" (7 Gauge) Deck
- Quick Attach

Cat. 4 driveline w/slip clutch



Shown with optional front chain guard



Smooth underdecks make for more efficient mowing and less area for rust to begin. Deck rings are standard.

## Specifications

Cutting Width . . . . . 96"  
 Transport Width . . . . . 102"  
 Overall Width . . . . . 102"  
 Overall Length . . . . . 97"  
 Overall Height . . . . . 2" - 15"  
 Blade Overlap . . . . . 3"  
 Hitch . . . . . QA Cat. II  
 Blade Carrier . . . . . Pan Stump Jumpers  
 Horsepower Required (min):  
 Lift . . . . . 50 hp

Main Gearbox  
 or Divider Box\* . . . . . 150 hp  
 Outboard Gearbox  
 or Center & Wings\* . . . . . 95 hp  
 Output Shaft Diameter . . 2-3/8"  
 Cut Capacity . . . . . 3"  
 Blade Tip Speed:  
 540 . . . . . 15,847 FPM  
 1000 . . . . . 15,847 FPM  
 Driveline Size: Quick Attach  
 Cat. 4 w/Slip Clutch  
 Deck Thickness . . . . . 3/16"

Side Skirt . . . . . 1/4" x 8"  
 Front Safety Deflectors . Chain Option  
 Rear Safety Deflectors:  
 Rubber Guard Standard with Chain Option  
 Weight (Approx): . . . . . 2175 lbs.  
 Standard Tires . . . . . Laminated  
 Dual Tailwheels . . . . . Option  
 Hydraulic Level  
 Lift . . . . . Standard  
 Offset Shift . . . . . 13" to curbside