

Superrr Sunshine 5', 6' & 7'

You're always ahead... with a Modern behind!

For more information or to locate a dealer call 1-800-231-8198



MODERN AG PRODUCTS, LTD.

5' CUTTING
WIDTH
60"

6' CUTTING
WIDTH
72"

7' CUTTING
WIDTH
84"



Splined input shaft
Slip clutch Standard.

Features:

- New heavy duty 3/8" Gearbox Plate
- Heavy duty stump jumper and laminated tailwheel
- Protected by a splined input shaft slip clutch standard
- Solid top weld • New smooth rounded rear deck
- Heavy duty tailwheel bracket and boom
- Double steel wall top edge
- One piece body with smooth top
- Upgraded 65 hp gearbox rating with 2"-15 spline output shaft
- Available Quick Attach

THE SUPERRR SUNSHINE IS A LONG LASTING CAT. 1 CUTTER WITH A CAT. 3 DRIVELINE.

Warranty

Provides a 3 year limited warranty on gearbox and 10 year limited warranty on deck rust thru on galvanized units only.



Shown with galvanized deck & frame option.



THESE COLORS ARE AVAILABLE ON THE 5', 6' & 7' SUPER SUNSHINE

Quick Attach Available (Unit Shown)



Smooth underdecks make for more efficient mowing and less area for rust to begin.



FRONT & REAR CHAIN GUARD OPTION



Specifications

Cutting Width	60" - 72" - 84"
Transport Width	65" - 75" - 88"
Overall Width	65" - 75" - 88"
Overall Length	100" - 106" - 122"
Cutting Height	2" - 10"
Hitch	Cat. 1 3 PT & Quick Attach
Blade Carrier	Pan Stump Jumpers
Quick Attach	Option

Horsepower Required (min):	
60"	25 hp
72"	30 hp
84"	40 hp
Gearbox Rating*	65 hp
Cut Capacity	2.5"
Blade Tip Speed:	
60"	16,519 FPM
72"	14,995 FPM
84"	17,300 FPM

Driveline Size	Cat. 3 w/Slip Clutch
Deck Thickness	3/16"
Slip Clutch Protection	Standard
Front Safety Deflectors	Chain Option
Rear Safety Deflectors:	
Rubber Guard Standard with Chain Option	
Weight (Approx)	725 lbs. - 865 lbs. - 1189 lbs.
Standard Tires	Laminated
Side Skirt	1/4" x 8"