

SPECIFICATIONS

Cooper TL550 Mobile Servicing Rig



Service Depth 20,000 (2 1/2" tubing)
Workover Depth 14,500 (2 7/8"/10.4# pipe)

DRAWWORKS

42" X 12" main drum	16" dia. X 38" long barrel
Line Size	1" (1 1/8" optional)
Brake Rim Cooling	Water Splash
Drum Clutch	PO 324
Brake Assist	48" x 10" disc
Drum Speed	5 Forward – 1 Reverse
42" x 8" Sand Drum	16" dia. x 43" long barrel
Line Size	9/16" 16,000" capacity
Drum Clutch	PO 224
New style 550hp	Right Angle Box

CARRIER

Axles	5ea (1 tag)
Cab	Single man
Fuel Tanks	2ea 100gal
Manufacturer	Dragon Rig Sales
Hydraulic Winch (1)	8000 lbs-Pullmaster PL8

ENGINE/ TRANSMISSION

Engine	Detroit Series 60/T3 Diesel
Rated Horse Power	500 HP (optional)
Transmission	Allison M-5610 Automatic
Drop Box	
Speeds	5 Forward – 1 Reverse



DERRICK	Dragon Mfg. Spec API 4F (type)
Height	104'
Number of lines	4/6/8
Hookload Capacity	250,000 lbs
Line Size	1" (1 1/8" optional)

Tubing Board, Rod Basket, Work Floor

TOAL WEIGHT LESS LINES & TOOLS 83,500#
MADE IN THE USA



DRAGON

PRODUCTS, LTD.

1-866-941-8198

www.modernusa.com